

VST MITSUBISHI MT 180D Specification

ENGINE

MODEL	K3C
Type	3 Cylinder, 4 Stroke, Over Head Valve
Bore	70mmn (2.75in)
Stroke	78mmn (3.07in)
Displacement (Swept Volume)	900cu.cm (54.9 cu.in)
Max. Torque	5.2kg-m (1900 rpm)
Output/Rated	18.5 hp/2799 rpm (IS: 10,000)
S.F.C. (specific Fuel Consumption)	230 gm/hp-hr
Cooling System	Water-cooled Radiator with compensatory tank
Dry Weight	125 kgs
Starting System	Starter Motor 12 Volts - 1.6KW

FUEL SYSTEM

Fuel	High Speed Diesel Oil (H.S.D)
Fuel Tank Capacity	18 liters
Air Cleaner	3 stage Oil Bath type

LIGHTING SYSTEM

Lighting	12 volts, 35 watts
Alternator	12 volts, 40 Amps
Glow Plug	12 volts Quick Hear Type

TRANSMISSION

Transmission	Selective Sliding Gear
Forward	6 Speeds
Reverse	2 Speeds with differential lock
Travelling Speed	1.2 kmph(min.)/14.0 kmph (max.)
Power Take Off (P.T.O)	13/8'' - SAE std Spline Shaft, 2 speeds 623, 919 & 1506 RPM at 2700 eng. rmp
Brake	Water proof internal expanding shoe type brake with parking brake

TRACTOR

Overall Dimensions	Width 1025mm, Height 1475mm Length 2565mm, Wheel Base 1422mm
Tyres	Front 5-12, Rear 8-18 Track Width 740, 890 mm
Ground Clearance	190 mm
Turning Radius	W/o Brake 2.5m & W/Brake 2.1m
Hauling	2 Wheel Trailer, 3 Tones (Gross weight)
Rotary	Side Drive Type, Width 1100mm
Weight	645kgs (W/o ballast weight)

PERFORMANCE

Tilling Width	1100mm
No. of Tines	28
Tilling Depth	150mm
Plough Depth	220mm

SPEEDS (Standard Pulley)

Forw L1	1.23 km/hr	Rever Low	1.58 km/hr
L2	1.87 km/hr		High 6.93 km/hr
L3	3.18 km		
H1	5.43 km/hr		
H2	8.22 km/hr		
H3	13.98 km/hr		



SALES REPRESENTATIVE :

IBERO-VIET NAM CO., LTD.

ADDRESS :Hamlet 3, Long Cang Commune Can Duoc Dist
Long An Province

TEL +84-72-372 6026/36

FAX +84-72-372 6056/57

EMAIL uan.do@ibero.vn

Do Duc Tuan (Mr)

tuyen.tran@ibero.vn

Tran Thanh Tuyen (Ms)